

▶ 15" LCD DISPLAY

X-15AV



▶ FEATURES

- Distinctive and modern design
- Metal housing with additional strength
- NeoV Optical Filter
- Swift 16ms response time
- High 500 brightness
- DVI ready for high quality signal
- S-Video and CVBS inputs (X-15AV only)
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	15.0" (381mm)	
	Max. Resolution	XGA 1024 x 768	
	Pixel Pitch	0.297mm	
	Brightness	500cd/m ² (Typical)	
	Contrast Ratio	400:1 (Typical)	
	Surface Treatments	Hard coating (3H), anti-glare treatment	
	Viewing Angle (H/V)	140°/120° (Typical)	
	Display Color	262,144	
	Response Time (R/F)	5ms / 11ms (Typical)	
Frequency (H/V)	H:	30kHz - 60kHz	
	V:	50Hz - 75Hz	
Input	Max. Pixel Clock	80MHz	
	Analog	15-Pin D-Sub	
	Digital (DVI-D)	29-Pin DVI	
	S-Video	4-Pin Mini Din S-Video	
	CVBS	CVBS Jack	
	Connector	Power	3-Pin AC Plug
		Thickness	3.0mm (0.18")
	NeoV Optical Filter	Reflection Rate	<1%
		Transmission Rate	>96%
		Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ 20°	
Mounting	VESA FPMPI	Yes (75mm)	
Dimensions	Net (W x H x D)	380 x 359 x 155 mm (15.0" x 14.1" x 6.1")	
	Packing (W x H x D)	445 x 490 x 225 mm (17.5" x 19.2" x 8.9")	
Weight	Net Weight	4.8Kg (10.6lbs)	
	Gross Weight	7.0Kg (15.4lbs)	
Regulation Approval	Safety & EMI	FCC, UL, CUL, EPA, CE, CB, TUV/BAURT, NORDIC, TCO 95, NUTEK, BSMI, ISO 13406, VCCI, CCC,	
		VESA	DDC 1/2B, DPMS
		Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <5W (Stand-by) <5W (Off)

* All specifications are subject to change without prior notice.

▶ CONTACT INFORMATION

BLOUDEX ELECTRONIC'S
 25, avenue Parmentier 75011 PARIS
 T: 01.48.05.12.12
 F: 01.48.05.66.32
www.bloudex.com