

► 19" LCD DISPLAY

# LCD19VGA



► FEATURES

- Slim 19.6mm bezel
- Super 700 contrast ratio
- Dual digital and analog inputs
- Built-in power supply
- Cable management organizer
- Kensington® security slot
- VESA standard wall mount
- Easy-to-use OSD
- Two available colors: black, ivory



► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	19.0" (482.6mm)
	<b>Max. Resolution</b>	SXGA 1280 x 1024
	<b>Pixel Pitch</b>	0.294mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	700:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (2H)
	<b>Viewing Angle (H/V)</b>	170°/170° (Minimum)
	<b>Display Color</b>	16.7M
	<b>Response Time (R/F)</b>	15ms / 10ms (Typical)
Inputs	<b>Frequency (H/V)</b>	H: 24kHz - 80kHz V: 50Hz - 75Hz
	<b>Max. Pixel Clock</b>	135MHz
Connector	<b>Life Time</b>	50,000hrs (Typical)
	<b>Analog</b>	15-Pin D-Sub
Tilt	<b>Digital (DVI-D)</b>	24-Pin DVI-D
	<b>Power</b>	3-Pin AC Inlet
Mounting	<b>Tilt</b>	0° ~ -20°
	<b>VESA FPMPMI</b>	Yes (100mm)
Dimensions	<b>Net (W x H x D)</b>	422 x 410 x 220mm (16.6" x 16.2" x 8.7")
	<b>Packing (W x H x D)</b>	502 x 496 x 154mm (19.8" x 19.5" x 6.1")
	<b>Weight</b>	
Regulation Approval	<b>Net Weight</b>	6.5Kg (14.3lbs)
	<b>Gross Weight</b>	8.5Kg (19.2lbs)
Power	<b>Safety &amp; EMI</b>	UL/CUL, TUV/GS, ISO 13406-2, TCO 99, FCC/B, VCCI, CE, BSMI
	<b>VESA</b>	DDC 1/2B, DPMS
Power Consumption	<b>Power AC</b>	100 - 240V, 50 - 60Hz
	<b>Consumption</b>	<80W (On) <3W (Stand-by) <3W (Off)

\* All specifications are subject to change without prior notice.

► CONTACT INFORMATION

**BLOUDEX ELECTRONIC'S**  
 25, avenue Parmentier 75011 PARIS  
 T: 01.48.05.12.12  
 F: 01.48.05.66.32  
[www.bloudex.com](http://www.bloudex.com)